

**AMENDMENTS TO THE CLAIMS:**

Please amend the claims to cancel Claims 1 - 11 and add new Claims 12 - 22 as follows, this listing of the claims will replace all prior versions, and listings, of claims in the application:

Claims 1 - 11 (Canceled)

12. (New) A device for producing a hot drink comprising:  
an appliance unit which is arranged in a receiving cavity while the device is in use as intended;  
a residual water tray which is arranged in the appliance unit while the device is in use as intended;  
a means for removing the appliance unit from the receiving cavity; and  
a means for removing the residual water tray from the appliance unit,  
wherein the means for removing the appliance unit from the receiving cavity and the means for removing the residual water tray from the appliance unit at least partly overlap.

13. (New) The device according to claim 12, wherein the means for removing the appliance from the receiving cavity comprises a first gripping surface arranged at the appliance unit and an opening at the appliance unit via which the first gripping surface is accessible, the means for removing the residual water tray from the appliance unit comprising a second gripping surface arranged at the residual water tray and the opening on the appliance unit via which the second gripping surface is accessible.

14. (New) The device according to claim 13, wherein the opening is disposed at an interface between a front wall of the residual water tray and a front wall of the housing, the second gripping surface being disposed on a first side of the opening on a rear side of the front wall of the residual water tray, the first gripping surface being disposed on a second side of the opening opposite the first side on the rear side of the front wall of the housing.

15. (New) The device according to claim 12, wherein the appliance unit is detachably anchored in the receiving cavity.

16. (New) The device according to claim 15, further comprising a detachable locking system disposed between the appliance unit and the receiving cavity.

17. (New) The device according to claim 16, wherein the locking system comprises a spring-loaded latching portion and an actuating surface which is accessible via the opening.

18. (New) The device according to claim 17, wherein the actuating surface is arranged in the gripping area of the first gripping surface.

19. (New) The device according to claim 16, wherein the locking system comprises a latching lever which tilts about a horizontal axis, the latching lever including a latching portion on its one arm and having an actuating surface on its other arm, which extends substantially parallel to the first gripping surface.

20. (New) The device according to claim 12, wherein the residual water tray is detachably anchored in a housing of the appliance unit.

21. (New) The device according to claim 12, wherein the residual water tray is anchored in the appliance unit by at least one of a positive and frictional inhibition.

22. (New) The device according to claim 12, wherein the device includes a built-in coffee machine.